

## Technical Specification | Contour 1.3

Sensitivity (2,83 V/1 m):	85 dB
Recommended Amp. Power:	Small size rooms > 30 W Medium size rooms > 80 W Large size rooms - W
IEC Total Power Handling:	> 150 W
Impedance, Nominal:	4 ohms
Impedance (20-200 Hz):	3,8 - 9,6 ohms
Impedance (200-20 kHz):	3,8 - 7,0 ohms
Impedance, Phase Shift (20-200 Hz):	-30,2 - 25,1
Impedance, Phase Shift (200 - 20 kHz):	-5,6 - 17,5
Impedance, HF (200 kHz):	8,1
Frequency Response (+/- 3 dB):	45 Hz - 22 kHz
Resonance Frequency:	43 Hz
Internal Cabinet Volume:	12 litres
Bass Principle:	Bass reflex
Weight:	8,7 kg
Dimensions (W x H x L):	204 x 380 x 293 mm
Crossover:	2 way
Crossover Frequencies:	2000 Hz
Crossover sloop:	Woofer: 6 dB/oct, tweeter: 6 dB/oct
Connection:	OCOS + Gold binding posts
Recommended placing:	Stand
Remarks:	<p><b>Tweeter:</b> 28 mm soft dome, magnetic fluid, aluminium front, pure aluminium wire voice coil, rear chamber.</p> <p><b>Woofer:</b> 17 cm with 75 mm pure aluminium wire voice coil, magnetically shielded.</p>

The crossover is impedance corrected.  
High quality polypropylene capacitors.  
Only high quality air coils are used.

### DYNAUDIO International GmbH

Ohepark 2  
21224 Rosengarten  
Germany  
Phone +49 (0)4108 - 4180 - 0  
Fax +49 (0)4108 - 4180 - 10  
E-Mail [info@dynaudio.de](mailto:info@dynaudio.de)