

## Technical Specification | Micron

Sensitivity (2.83 V/1 m):	82 dB
Recommended Amp. Power:	Small size rooms: >60 watts Medium size rooms: >150 watts Large size rooms: -- watts
IEC Long Term Power Handling:	>150 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.8 - 7.9 ohms
Impedance, (200 - 20 kHz):	5.6 - 6.7 ohms
Impedance, Phase Shift (20 - 200 Hz):	-21.5° - +20.4°
Impedance, Phase Shift (200 - 20 kHz):	-3.3° - +17.4°
Impedance, HF (200 kHz):	5.9 ohms
Frequency Response (+/- 3.5 dB):	55 Hz - 21 kHz
Resonance Frequency:	72 Hz
Internal Cabinet Volume:	7.7 litres
Bass Principle:	Closed
Weight:	6.8 kg
Dimensions (W x H x L):	170 x 283 x 305 mm
Crossover:	2 way. Crossover is impedance corrected
Crossover Frequencies:	1500 Hz
Crossover Slope:	Woofer: 6 dB/oct, Tweeter: 6 dB/oct
Connection:	Gold binding posts
Recommended Placing:	Wall, book shelf
Remarks:	<p>Tweeter: 28 mm soft dome. Magnetic fluid. Aluminium front. Pure aluminium wire voice coil. Rear chamber.</p> <p>Woofer: 15 cm with 75 mm pure aluminium wire voice coil. Die cast basket.</p> <p>High quality polypropylene capacitors. Only high quality air coils are used. Designed for wall or shelf mounting. Wall spikes included.</p>

### DYNAUDIO International GmbH

Ohepark 2  
21224 Rosengarten  
Germany  
Phone +49 (0)4108 - 4180 - 0  
Fax +49 (0)4108 - 4180 - 10  
E-Mail [info@dynaudio.de](mailto:info@dynaudio.de)