

Technical Specification | Audience 72

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power: Small size rooms:	>25 watts
Medium size rooms:	>65 watts
Large size rooms:	>125 watts
IEC Long Term Power Handling:	210 watts
Impedance, Nominal:	4 ohms
Impedance, (20-200 Hz):	3.1 - 7.2 ohms
Impedance, (200-20 kHz):	3.8 - 7.8 ohms
Impedance, Phase Shift (20-200 Hz):	-20° - +28°
Impedance, Phase Shift (200-20 kHz):	-4° - +28°
Impedance, HF (200 kHz):	11 ohms
Frequency Response (+/- 3 dB):	28 Hz - 24 kHz
Resonance Frequency:	34 Hz
Internal Cabinet Volume:	29 litres
Bass Principle:	Bass reflex
Weight:	17.7 kg
Dimensions (W x H x L):	204 x 959 x 256 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	180 and 2600 Hz
Crossover Slope:	Woofers 6 dB/oct; Tweeter 12 dB/oct
Connection:	CE compliant insulated gold binding posts
Recommended Placing:	Floor

Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. Pure aluminium wire voice coil. Rear chamber.
	Woofers: 2 x 17 cm polypropylene cone. 75 mm pure aluminium wire voice coil.
	Cabinet: Front baffle 28 mm MDF. Port plugs and spikes included. Bitumen damped enclosure.

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de