

## Technical Specification | Confidence 3

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: -- watts Medium size rooms: >65 watts Large size rooms: >125 watts
IEC Long Term Power Handling:	200 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	4.4 - 10.7 ohms
Impedance, (200 - 20 kHz):	4.7 - 6.3 ohms
Impedance, Phase Shift (20 - 200 Hz):	-28.8° - +20.4°
Impedance, Phase Shift (200 - 20 kHz):	-3.8° - +8.3°
Impedance, HF (200 kHz):	5.3 ohms
Frequency Response (+/- 3 dB):	38 Hz - 28 kHz
Resonance Frequency:	35 Hz
Internal Cabinet Volume:	19 litres
Bass Principle:	Bass reflex
Weight:	17 kg
Dimensions (W x H x L):	226 x 492.5 x 336 mm
Crossover:	2 way. Crossover is impedance corrected
Crossover Frequencies:	2600 Hz
Crossover Slope:	Woofer: 6 dB/oct, Tweeter: 6 dB/oct
Connection:	OCOS + WTB gold binding posts
Recommended Placing:	On the included stand
Remarks:	<p>Tweeter: ESOTAR, 28 mm state-of-the-art soft dome tweeter. Pure aluminium wire voice coil.</p> <p>Woofer: Powerful 20 cm with 75 mm pure aluminium wire voice coil. Neodymium magnet system. Die cast basket.</p> <p>High quality polypropylene capacitors. Only high quality air coils are used. Special multi core air coils. Sandwich enclosure. Dedicated stand with spikes.</p>

**DYNAUDIO International GmbH**

Ohepark 2  
21224 Rosengarten  
Germany  
Phone +49 (0)4108 - 4180 - 0  
Fax +49 (0)4108 - 4180 - 10  
E-Mail [info@dynaudio.de](mailto:info@dynaudio.de)