

Technical Specification | Contour 1.1

Sensitivity (2.83 V/1 m):	85 dB
Recommended Amp. Power:	Small size rooms: >30 watts Medium size rooms: >80 watts Large size rooms: -- watts
IEC Long Term Power Handling:	>150 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.9 - 12.2 ohms
Impedance, (200 - 20 kHz):	3.9 - 8.3 ohms
Impedance, Phase Shift (20 - 200 Hz):	-35.7° - +33.0°
Impedance, Phase Shift (200 - 20 kHz):	-3.6° - +23.0°
Impedance, HF (200 kHz):	8.5 ohms
Frequency Response (+/- 2.5 dB):	47 Hz - 30 kHz
Resonance Frequency:	55 Hz
Internal Cabinet Volume:	8.5 litres
Bass Principle:	Bass reflex
Weight:	6.5 kg
Dimensions (W x H x L):	170 x 316 x 283 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	1900 Hz
Crossover Slope:	6 dB/oct
Connection:	OCOS + Gold binding posts
Recommended Placing:	Stand (wall and book shelf with port plugs)
Remarks:	<p>Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die-cast aluminium front. Pure aluminium wire voice coil. Rear chamber.</p> <p>Woofers: 15 cm with die cast basket and 38mm pure aluminium wire voice coil.</p> <p>High quality polypropylene capacitors. Port plugs included.</p>

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de