

Technical Specification | Contour 1.3 MK II

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: >25 watts Medium size rooms: >65 watts Large size rooms: -- watts
IEC Long Term Power Handling:	150 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.5 - 14.4 ohms
Impedance, (200 - 20 kHz):	3.6 - 7.6 ohms
Impedance, Phase Shift (20 - 200 Hz):	-42.6° - +25.3°
Impedance, Phase Shift (200 - 20 kHz):	-8.4° - +20.2°
Impedance, HF (200 kHz):	5.0 ohms
Frequency Response (+/- 2.5 dB):	43 Hz - 24 kHz
Resonance Frequency:	41 Hz
Internal Cabinet Volume:	12 litres
Bass Principle:	Bass reflex
Weight:	8.9 kg
Dimensions (W x H x L):	204 x 380 x 293 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	2600 Hz
Crossover Slope:	6 dB/oct
Connection:	Dynaudio Terminal with WBT gold binding posts
Recommended Placing:	Stand (wall and book shelf with port plugs)
Remarks:	<p>Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die cast aluminium front. Pure aluminium wire voice coil. Rear chamber.</p> <p>Woofers: 17 cm with die cast basket and polypropylene cone. Cone and dust cabmoulded as one piece. 75 mm pure aluminium wire voice coil wound on capton former.</p> <p>High quality polypropylene capacitors. Only high quality air coils are used. Port plugs included.</p>

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de