

Technical Specification | Contour 1.8 MK II

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: >30 watts Medium size rooms: >70 watts Large size rooms: >130 watts
IEC Long Term Power Handling:	250 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.8 - 9.4 ohms
Impedance, (200 - 20 kHz):	4.6 - 5.8 ohms
Impedance, Phase Shift (20 - 200 Hz):	-22.2° - +28.8°
Impedance, Phase Shift (200 - 20 kHz):	-0.6° - +9.3°
Impedance, HF (200 kHz):	7.6 ohms
Frequency Response (+/- 2 dB):	38 Hz - 20 kHz
Frequency Response (+/- 3.5 dB):	28 Hz - 30 kHz
Resonance Frequency:	27 Hz
Internal Cabinet Volume:	32.5 litres
Bass Principle:	Bass reflex
Weight:	19 kg
Dimensions (W x H x L):	204 x 935 x 294 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	2600 Hz
Crossover Slope:	Woofer: 6 dB/oct, Tweeter: 6 dB/oct
Connection:	Dynaudio Terminal with WBT gold binding posts
Recommended Placing:	Floor, free standing
Remarks:	<p>Tweeter: 28 mm soft dome. Magnetic fluid. Aluminium front. Pure aluminium wire voice coil. Rear chamber. Double magnet system.</p> <p>Woofer: 2 x 17 cm with 75 mm pure aluminium wire voice coil. Die cast basket. Magnetically shielded.</p> <p>High quality polypropylene capacitors. Portplugs and Spikes included.</p>

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de