

## Technical Specification | Contour 3.0

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: -- watts Medium size rooms: >65 watts Large size rooms: >125 watts
IEC Long Term Power Handling:	200 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.4 - 10.2 ohms
Impedance, (200 - 20 kHz):	4.8 - 9.6 ohms
Impedance, Phase Shift (20 - 200 Hz):	-36.0° - +21.0°
Impedance, Phase Shift (200 - 20 kHz):	+1.0° - +22.2°
Impedance, HF (200 kHz):	9.8 ohms
Frequency Response (+/- 3 dB):	30 Hz - 21 kHz
Resonance Frequency:	30 Hz
Internal Cabinet Volume:	47 litres
Bass Principle:	Bass reflex
Weight:	34 kg
Dimensions (W x H x L):	222 x 1060 x 366 mm
Crossover:	3 way
Crossover Frequencies:	400 Hz + 2300 Hz
Crossover Slope:	Woofers: 6 dB/oct, Midrange: 6 dB/oct, Tweeter: 6 dB/oct
Connection:	Dynaudio Terminal with WBT gold binding posts
Recommended Placing:	Floor, free standing
Remarks:	<p>Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die cast aluminium front. Pure aluminium wire voice coil. Rear chamber.</p> <p>Midrange: 15 cm with die cast basket and polypropylene cone. Cone and dust cap moulded as one piece. 38 mm pure aluminium wire voice coil.</p> <p>Woofers: 20 cm with die cast basket and polypropylene cone. Cone and dust moulded as one piece. 75 mm pure aluminium wire voice coil wound on capton former.</p> <p>High quality polypropylene capacitors. Port plugs and Spikes included. Sandwich enclosure.</p>

### DYNAUDIO International GmbH

Ohepark 2  
21224 Rosengarten  
Germany  
Phone +49 (0)4108 - 4180 - 0  
Fax +49 (0)4108 - 4180 - 10  
E-Mail [info@dynaudio.de](mailto:info@dynaudio.de)