

Technical Specification | Contour 3.3

Sensitivity (2.83 V/1 m):	88 dB
Recommended Amp. Power:	Small size rooms: -- watts Medium size rooms: >40 watts Large size rooms: >80 watts
IEC Long Term Power Handling:	300 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.2 - 9.8 ohms
Impedance, (200 - 20 kHz):	6.4 - 8.0 ohms
Impedance, Phase Shift (20 - 200 Hz):	-30.9° - +30.0°
Impedance, Phase Shift (200 - 20 kHz):	-6.0° - +25.6°
Impedance, HF (200 kHz):	6.5 ohms
Frequency Response (+/- 2.5 dB):	32 Hz - 20 kHz
Resonance Frequency:	32 Hz
Internal Cabinet Volume:	Woofers: 2 x 26 litres, Midrange: 2.8 litres
Bass Principle:	Bass reflex
Weight:	36.5 kg
Dimensions (W x H x L):	222 x 1187 x 366 mm
Crossover:	3 way
Crossover Frequencies:	350 Hz + 2.3 kHz
Crossover Slope:	Woofers: 6 dB/oct, Midrange: 6 dB/oct, Tweeter: 6 dB/oct
Connection:	Dynaudio Terminal with WBT gold binding posts
Recommended Placing:	Floor, free standing
Remarks:	<p>Tweeter: 28 mm soft dome. 4 mm die cast aluminium front. Magnetic fluid. Pure aluminium wire voice coil.</p> <p>Midrange: 15 mm with die cast basket and polypropylene cone. Cone and dome moulded in one piece. 38 mm pure aluminium wire voice coil.</p> <p>Woofers: 20 cm with die cast chassis and polypropylene cone. Powerful 100 mm internal magnetsystem. Vented through magnet and under spider.</p> <p>Portplugs and Spikes included.</p>

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de