

Technical Specification | Contour Center

| | |
|--|--|
| Sensitivity (2.83 V/1 m): | 86 dB |
| Recommended Amp. Power: | Small size rooms: >25 watts Medium size rooms: >65 watts Large size rooms: >130 watts |
| IEC Long Term Power Handling: | 150 watts |
| Impedance, Nominal: | 6 ohms |
| Impedance, (20 - 200 Hz): | 4.1 - 7.1 ohms |
| Impedance, (200 - 20 kHz): | 4.1 - 6.2 ohms |
| Impedance, Phase Shift (20 - 200 Hz): | -19.4° - +12.2° |
| Impedance, Phase Shift (200 - 20 kHz): | -1.0° - +11.1° |
| Impedance, HF (200 kHz): | 7.9 ohms |
| Frequency Response (+/- 2 dB): | 80 Hz - 21 kHz |
| Resonance Frequency: | 85 Hz |
| Internal Cabinet Volume: | 16.8 litres |
| Bass Principle: | Variovent |
| Weight: | 11.1 kg |
| Dimensions (W x H x L): | 570 x 165 x 320 mm |
| Crossover: | 2 way. The crossover is impedance corrected |
| Crossover Frequencies: | 2600 Hz |
| Crossover Slope: | Woofer: 6 dB/oct, Tweeter: 6 dB/oct |
| Connection: | Dynaudio Terminal with WBT gold binding posts |
| Recommended Placing: | Above or below TV/Videoscreen |
| Remarks: | <p>Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die cast aluminium front. Pure aluminium wire voice coil. Magnetically shielded double magnet system. Rear chamber.</p> <p>Woofer: 15 cm with polypropylene cone. 75 mm pure aluminium wire voice. Magnetically shielded. Vented magnet system.</p> <p>Only high quality air coils are used.</p> |

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de