

## Technical Specification | Contour T 2.1

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: 22 watts Medium size rooms: 63 watts Large size rooms: 123 watts
IEC Long Term Power Handling:	200 watts
Impedance, Nominal:	6 ohms
Impedance, (20 - 200 Hz):	4.3 - 11.6 ohms
Impedance, (200 - 20 kHz):	4.4 - 7.1 ohms
Impedance, Phase Shift (20 - 200 Hz):	-31,2° - +24,8°
Impedance, Phase Shift (200 - 20 kHz):	-5° - +14,5°
Impedance, HF (200 kHz):	7.5 ohms
Frequency Response (+/- 3 dB):	32 Hz - 25 kHz
Resonance Frequency:	34 Hz
Internal Cabinet Volume:	22.5 litres
Bass Principle:	Reflex
Weight:	13.1 kg
Dimensions (W x H x L):	570 x 204 x 300 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	1800 Hz
Crossover Slope:	Woofer 6 dB/oct, Tweeter 6 dB/oct
Connection:	WBT CE-compliant gold binding posts
Recommended Placing:	Stand
Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die cast aluminium front. Pure aluminium wire voice coil. Rear chamber. Double magnet.  Woofer: 17 cm one-piece moulded polypropylene cone. 75 mm pure aluminium wire voice coil  Cabinet: 19 mm MDF, front baffle 22 mm MDF  System: High quality polypropylene capacitors. Port plug included.

### DYNAUDIO International GmbH

Ohepark 2  
21224 Rosengarten  
Germany  
Phone +49 (0)4108 - 4180 - 0  
Fax +49 (0)4108 - 4180 - 10  
E-Mail [info@dynaudio.de](mailto:info@dynaudio.de)